

Norton® TH 16011

UL Underwriters Laboratories Inc. certificate

SAINT-GOBAIN
PERFORMANCE PLASTICS
Distributor Norton® TH
Dr. D. Müller GmbH

Component - Plastics

E231847

TAIMIDE TECHNOLOGY INC

127 WENDER RD, SEC 3, SHINPU JEN HSIINCHU HSIEN 305 TW

TH

Polyimide (PI), furnished as film

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
NC	0.012	V-0	-	-	130	-	130
	0.014	V-0	0	4	220	-	220
	0.025	V-0	0	4	220	-	220
	0.05	V-0	0	4	220	-	220
	0.075	V-0	0	4	220	-	220
	0.125-0.138	V-0	0	3	220	-	220

Comparative Tracking Index (CTI): 3

High-Voltage Arc Tracking Rate (HVTR): -

Dielectric Strength (kV/mm): -

Dimensional Stability (%): -

High Volt, Low Current Arc Resis (D495): -

Volume Resistivity (10^x ohm-cm): -

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2002-10-31

Last Revised: 2007-09-13

Underwriters Laboratories Inc®



IEC and ISO Test Methods

Test Name	Test Method	Units	Thickness Tested (mm)	Value
IEC Flammability	IEC 60695-11-10	Class (color)	0.012	V-0 (NC)
			0.014	V-0 (NC)
			0.025	V-0 (NC)
			0.05	V-0 (NC)
			0.075	V-0 (NC)
			0.125-0.138	V-0 (NC)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-

Norton® ist ein eingetragenes Markenzeichen der Firma Saint-Gobain Performance Plastics



SAINT-GOBAIN
PERFORMANCE PLASTICS
Distributor Norton® TH
Dr. D. Müller GmbH